

VHB436

Battery-Powered Industrial Vacuum

– Lithium-ion technology for mobility and peak performance





“Achieve peak performance by selecting 2 or 3 lithium-ion batteries for more than 2 hours of continuous runtime.”

Lose the cord, enhance the benefits

Maximise industrial mobility, performance, and runtime

Nilfisk's first battery-powered industrial vacuum delivers speed, power and efficiency to your cleaning regimen. Now you can easily clean high-traffic areas and tight or out-of-reach spaces without the restrictions of a power cable.

Efficient and effective

- Modular, fast-charging lithium-ion battery
- No cable to hinder movement

Safe and smart

- Minimise the risk of trips or falls over the power cable
- HEPA filtration options safely capture potentially hazardous dusts
- Reduce risk of operator exposure with Longopac® collection system
- Compliant with EU electrical-safety regulations

Versatile and adaptable

- Clean where electrical outlets are scarce, or cables pose a safety risk
- Powerful enough to clean overhead racks, shelves and beams
- Optional forklift bracket for machine elevation and transport
- Wide range of accessories easily stored in the optional accessory holder

Unbeatable productivity

Lithium-ion batteries enables the lighter, cable-free VHB436 to effectively clean more of your facility in less time. When it needs recharged, just plug it in and the fast-charging capability means cleaning can resume again quickly.


Uncompromising performance

Unlike other battery-powered industrial vacuums, the VHB436 doesn't trade power for convenience. Its 36V battery-powered solution, top-grade industrial suction and reliable filter performance take care of challenging dust, dirt, and debris from floor to ceiling, indoors or outdoors.



Benefits of our Lithium-Ion Technology

- Fast-charging capability: Go from 0 to 90% capacity in just 2 hours
- Optimal uptime: Easy service with redundant, swappable battery modules
- Superior lifespan: Up to 7 years and 1500+ charge-discharge cycles
- IoT connectivity: Battery Management System tracks and logs performance





Technical specifications

Description	VH436 UKP	VHB436 3B UKP
Battery type	Lithium-ion	Lithium-ion
Battery quantity	2	3
Output battery voltage (V)	36	36
Battery run time (min.)	93	147
Battery charge time (100%) (min.)	200	270
Battery charge time (90%) (min.)	120	180
Voltage (charge mode) (V)	110-240	110-240
Frequency (charge mode) (Hz)	50/60	50/60
Insulation Class	III	III
Rated power (kW)	2.4	2.4
Airflow with hose D70 – 3 M (L/min – m ³ /h)	6333 – 380	6333 – 380
Vacuum max. (mBar)	130	130
Sound pressure level (dB(A))	71	71
Container capacity (L)	50**	50**
Main filter area (cm ²)	19,500	19,500
HEPA filter area (cm ²)	35,000	35,000
Inlet (mm)	70	70
Length x Width x Height (cm)	105 x 60 x 125	105 x 60 x 125
Weight (kg)	125	135
Cable length (charger) (m)	3	3
Item number	4022500003	4022500004

*specifications subject to change

**100L is available upon request

Nilfisk Ltd

Nilfisk House · Bowerbank Way
 Gilwilly Industrial Estate
 Penrith · Cumbria · CA11 9BQ

Tel. 01768 868995 (UK) · 01 294 3838 (IE)
 sales.uk@nilfisk.com
 www.nilfisk.co.uk · www.nilfisk.ie

